Optional Items









Applications






t Prevention Window	Air Compressor Unit	Fume Extraction System	Acrylic Cutting	Stamp Engraving	Tile Engra
Venus II		VII-12			
Laser Source		12W			
		Sealed CO2 Laser			
Cooling		Air-cooled, Operating environment temperature 15°-30°C (60° - 86°F)			
Work Area		11.8 x 8.2 in. (300 x 210 mm)			
Max.Part Size (W	x L x H)	14.2 x 11.8 x 2.8 in. (360 x 300 x 70 mm)			
Dimensions (W x D x H)		24.4 x 17.1 x18.1 in. (610 x 435 x 460 mm)			
Weight		32 Kg / 70 lb			
Drive		Closed-loop DC Servo Control			
Maximum Speed*		20IPS			
Throughput*		110.7 in ² / hr (714.1 cm ² / hr)			
Speed Control		Adjustable from 0.1~100% (Up to 16 color-linked speed settings per job)			
Power Control		Adjustable from 0~100% (Up to 16 color-linked power settings per job)			
Engraving Capability		256-level gray scale image processing capability			
Distance Accuracy		0.254 mm or 0.1% of move, whichever is greater			
Z-Axis Movement		Automatic			
Focus Lens		Standard 1.5", optional 2.0" available			
Resolution (DPI)		Available 200, 250, 300, 500, 600, 1000			
Computer Interface		10 Base-T Ethernet, Full speed 2.0 USB			
Compatible Operating Systems		MS Windows			
Display Panel		4-line LCD panel showing current file name, total working time, laser power, engraving speed, file(s) loaded into memory buffer, setup and diagnostic menus			
Safety		Class I Laser Product Compliant with EN60825 Class II Laser Product Compliant with CDRH			
Standard Feature	S				
Auto Focus		✓			
Red Dot Pointer			4		
3D and Stamp Mode		✓			
Reserved Stamp Jig		→			
Fume Extraction System		External exhaust system with minimum flow rate 215m³/h (CFM 125 ft³/h) is required, 10kPA negative pressure (Purex GCC 400 @ 2" exhaust port)			
Operation Voltage		100- 240VAC, 50-60Hz Auto Switching, Max. 7A			

^{*} Speed is not equal to throughput. See dealer or visit www.GCCworld.com for more details.









Authorized Dealer













GCC Headquarters 4F-1, No.236, Fude 2nd Rd., Xizhi Dist., New Taipei City 22151, Taiwan 886-2-6616-6692 Fax: 886-2-2694-6875 No.1, Chen Feng Road, Yushan, Kunshan, Jiangsu 215300, China 86-512-5726-1515 Fax: 86-512-5726-1518 GCC Europe B.V. Eglantierbaan 43-45, 2908 LV, Capelle a/d IJssel, The Netherlands 31-10-458-9367 Fax: 31-10-451-9874 GCC America, Inc 20453 E Valley Blvd. Walnut, CA 91789, USA

1-909-718-0248 Fax: 1-909-718-0251 US & Canada Only Toll Free: 1-888-284-5211



Laser Engraver

CC LaserPro Venus II

Micro in Size, Macro in Capability









- The most compact laser engraver
- Standard Auto Focus gauge for precise focal length and delicate laser output
- · Air ventilation designs for stamp making industry
- Window-based driver interface for easy operation
- User friendly and intuitive interface
- LaserPro DirectPrint MAC AI Plug-In available for use with MAC OS
- Drag and Engrave feature assures remarkably easy and fast set-ups

^{*}The flow rate is determined by a default fume extraction system; the flow rate may vary due to a different fume extraction system

 $[\]Delta$ Specifications are subject to change without prior notice.