

ŠTANDARDNÉ

POTLAČITEĽNÉ

PRENOS	Teplota (°C)	160	130	150	160	130	Standard 160 150 130	Nylon*	150	160	160	160	160	150	160	160	160	160	160	160	160	160	Standard 160 150 130	Nylon*	150	160	160	160	150	130	160	160	160	160	160	160	160	160	
	Prítlak (bar)	2,5 – 3,0	2,5 – 3,0	2,0	2,5 – 3,0	2,5 – 3,0	2,5 – 3,0	2,0	2,0	2,0	2,0	2,5 – 3,0	2	3,0	2,5 – 3,0	2,5 – 3,0	2,5 – 3,0	2,5 – 3,0	2,5 – 3,0	2,5 – 3,0	2,5 – 3,0	2,5 – 3,0	2,5 – 3,0	2,0	2,5 – 3,0	2,5 – 3,0	2,5 – 3,0	2,5 – 3,0	2,0	2,5 – 3,0	2,5 – 3,0	2,5 – 3,0	2,5 – 3,0	2,5 – 3,0	2,5 – 3,0	2,5 – 3,0			
	Čas (sec.)	15	5	Pre- pressing 4 Second pressing 10	15	10	3 4 5	5 + 5 + 10*	15	15	15	15	Pre- pressing 4 Second pressing 10	25	15 Second pressing 3	15	15	15	15	15	15	15	3 4 5	5 + 5 + 10*	15	15	15	15	Pre- pressing 4 Second pressing 10	5	15	15	15	15	15	15	15		
	Strhávanie (za tepla = W / za studena = C)	W	W	W	W	W	W & C	W & C	W	C	W	W	W	C	C	C	C	W	W	W	C	W	W	W	W	W	W	W	W	W	W	W	W	W	W	W	W		
PRANIE	Pranie (°C)	80	60	40	80	40	60	40	60	40	40	60	40	60	40	Hand- wash only	60	60	60	60	40	60	60	60	40	80	60	40	40	40	60	40	60	60	60	40	90	60	40
	Sušička	●	●	●	●	●	●**	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●**	●	●	●	●	●	●	●	●	●	●	●	●	●	●		
	Čistiareň	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●		
		*POLI-FLEX * TURBO & TURBO PRINT • Pre-pressing 5 sec. • Pressing on Nylon 5 sec. • After Removing PET Liner 10 sec. ** POLI-FLEX * TURBO TURBO PRINT commercial tumble dryer up to 100°C																																					
11/04/2024																																							

* POLI-FLEX * TURBO
& TURBO PRINT
• Pre-pressing 5 sec.
• Pressing on Nylon 5 sec.
• After Removing PET
Liner 10 sec.

** POLI-FLEX * TURBO
TURBO PRINT
commercial tumble
dryer up to 100°C